

INTERNATIONAL SOCIETY FOR SOIL MECHANICS AND GEOTECHNICAL ENGINEERING



This paper was downloaded from the Online Library of the International Society for Soil Mechanics and Geotechnical Engineering (ISSMGE). The library is available here:

<https://www.issmge.org/publications/online-library>

This is an open-access database that archives thousands of papers published under the Auspices of the ISSMGE and maintained by the Innovation and Development Committee of ISSMGE.

ated homogeneous samples did not permit to obtain samples of the same water-content throughout their entire height, because of the friction on the sides.

The variation of water-content observed on a length of 10 or 12 cm (4" to 5") could reach 20% of the average value.

Remoulded homogeneous samples were obtained from dry pulverized clay.

The dry powder is compressed with 2 pistons in a permeable cylinder. This compressed sample is brought into contact with water. The water is absorbed and one awaits consolidation.

The samples thus obtained presented no stratification, their water-content was constant throughout their height, their apparent specific gravity agreed with their water-content.

6) Results obtained

The water-contents in terms of consolidation

pressures are:

34.5 %	for	4 kg/cm ²	(57 psi)
32.2 %	"	6 kg/cm ²	(85.7 psi)
31 %	"	8 kg/cm ²	(115.7 psi)
29.5 %	"	10 kg/cm ²	(143.8 psi)

For all the consolidation pressures the intrinsic curves, obtained with the triaxial device, show an inclination of 10°. This value corresponds to that which may be derived from the slope of the shearing planes or from shearing due to torsion.

Cohesion which may be derived from the intrinsic curves is of 1.5 kg/cm² (21.4 psi) and 2 kg/cm² (28.5 psi), the consolidation pressures being respectively 6 kg/cm² (85.7 psi) and 10 kg/cm² (143.8 psi).

Series of tests are now being carried out with a view to measuring the variations of water-content and cohesion.

-o-o-o-o-o-o-o-

SETTLEMENTS DEDUCTED FROM OEDOMETER TESTS COMPUTATION HYPOTHESIS AND TRIAXIAL TESTS

Il d 15

M. BUISSON

Ingénieur E.P. Paris

SUMMARY OF THE FRENCH REPORT

When computing from oedometer tests, the figures obtained for settlements are in most cases larger than when such settlements are directly obtained from existing buildings.

These differences must proceed from a definite cause which we are, now, to work out.

After systematical tests, we should think these differences related to the wrong value given to Poisson's number in such computations.

In oedometer test calculations, the value assumed for the said Poisson's number is "nil". In fact, we don't know the real value, but, as the "nil" value is certainly wrong the calculations must be, and are, widely away from the true figures.

In practice, the estimated settlements are always in excess to the recorded ones, moreover, when the computer adds to the calculated figure the settlements which must take place just when the soil is loaded, although no volumetric change has to occur in the latter process.

An experimental determination of the exact value of Poisson's number is a shear necessity and it must be as true as possible, relating to the prevailing conditions in loaded soils.

In a tentative way, experiments have been performed on cubic samples, full of water but being drained on every side. Each sample side had applied to it, a given and measured pressure, and the correlative deformations were recorded.

This "triaxial" apparatus may be used when testing various samples of underground

soils, the particles of which may be much large than when using the usual oedometer apparatus.

The actual process includes two specific main tests, i.e. :

- 1) Compressive tests, in which lateral sides of the sample are maintained in a fixed position, and
- 2) Crushing tests, in which a fixed and constant pressure is applied to such lateral sides.

In both tests, and first of all, the swelling pressure has to be measured.

From obtained data, may be deducted :

- 3) the figures for compression modulus and Poisson's number which may be accounted for, when precise calculations are to be made referring to settlements in same soils as samples.
- 4) The crushing stresses in relation with given horizontal stresses, from which, in using Mohr's circles envelope line, one may deduct an internal friction angle and a cohesion value.

The formulas here after given, may enable any designer to get from such tests results, the corresponding values for the compression modulus and Poisson's number when using this "triaxial" apparatus in various ways.

The recorded test results are not yet sufficient in number to get a definite opinion as to the exactitude of a similar test method. Any way, up to know, it has given interesting data for the actual behavior in loaded soils.

-o-o-o-o-o-o-o-