

INTERNATIONAL SOCIETY FOR SOIL MECHANICS AND GEOTECHNICAL ENGINEERING



This paper was downloaded from the Online Library of the International Society for Soil Mechanics and Geotechnical Engineering (ISSMGE). The library is available here:

<https://www.issmge.org/publications/online-library>

This is an open-access database that archives thousands of papers published under the Auspices of the ISSMGE and maintained by the Innovation and Development Committee of ISSMGE.

The paper was published in the proceedings of the 7th International Conference on Earthquake Geotechnical Engineering and was edited by Francesco Silvestri, Nicola Moraci and Susanna Antonielli. The conference was held in Rome, Italy, 17 - 20 June 2019.

Field measurements of linear and nonlinear shear moduli during large-strain shaking

B. Zhang, K.H. Stokoe & F. Menq

Civil, Architectural and Environmental Engineering Department, The University of Texas at Austin, Austin, TX, USA

ABSTRACT: An improvement to the field liquefaction testing method that presently involves one large mobile shaker is under development. The improvement is designed to permit determination of both linear and nonlinear shear moduli of soils during large-strain, horizontal shaking. The improved method requires two mobile shakers to simultaneously excite an embedded sensor array. Small-amplitude, high-frequency motions (160 Hz) are generated with a smaller shaker (Thumper). These motions are superimposed on larger-amplitude, lower-frequency motions (25 Hz) generated with a larger shaker (Rattler). By operating the shakers at different frequencies in perpendicular directions, small-strain shear moduli can be determined many times (>6) during each cycle of larger-strain shaking. The Spectral-Analysis-of-Body-Waves (SABW) method is implemented to continuously evaluate the small-strain shear moduli. These initial tests show that the soil skeleton can effectively be studied during larger-strain cycling. The overall goal is to improve field characterization of soils undergoing nonlinear loading processes.

1 INTRODUCTION

For the past 14 years, large hydraulic mobile shakers operated by the University of Texas with funding from the National Science Foundation (NSF) have been used to perform nonlinear shaking tests in the field to study the initiation and generation of pore-water pressure leading to soil liquefaction. The current field testing approach involves using one, large mobile shaker to dynamically load the surface of a natural soil deposit with a series of increasing, horizontal-shaking amplitudes. Simultaneously, the motions and pore-water pressure responses are measured at depth in the soil using an embedded array of sensors (Rathje et al. 2005, Cox et al. 2009, Stokoe et al. 2014 and Roberts et al. 2017). The objectives of the field shaking tests are: (1) to measure the excess pore-water pressure generation, and (2) to determine the associated nonlinear shear moduli of the natural sandy deposits as functions of induced cyclic shear strain and number of loading cycles.

During the process of pore-water pressure generation leading to soil liquefaction, the reduction in the shear modulus results from the coupled effects of two processes: (1) the increasing nonlinearity in the soil skeleton as shear strain increases, and (2) the decreasing mean effective confining pressure as pore-water pressure builds up. In an attempt to better understand and characterize this complex behavior, it is important to develop a field method with which both linear and nonlinear shear moduli of the soil are determined during large-strain shaking tests. In this initial effort to develop this testing method, a field site with unsaturated clayey soil was selected, and field tests involving numerous low-amplitude to high-amplitude shaking tests were conducted without the added complications of excess pore-water pressure generation.

In this study, two mobile shakers, named Rattler and Thumper, that are available at the NHERI@UTexas equipment facility (Stokoe et al. 2017), were simultaneously used to horizontally load an instrumented soil zone within 1 to 1.5 m of the ground surface. During field testing, Thumper was used to shake the ground surface at 160 Hz with a small force level. At

the same time, Rattler was used to shake the ground surface at 25 Hz over a range of higher force levels. The Spectral-Analysis-of Body-Waves (SABW) method (Kim 2012) was used to determine the variation of small-strain shear moduli (using the high-frequency, small-strain shear waves induced by Thumper) during the low-frequency, large-strain cyclic loading induced by Rattler. The SABW method and the effects of high-amplitude shearing cycles on the small-strain shear moduli measured at a test site of unsaturated clayey soil in Austin, TX, are presented in this paper.

2 FIELD TEST SITE

Over the past 30 years, many experimental field projects involving soil dynamics and geotechnical earthquake engineering projects have been conducted at the Hornsby Bend Biosolids Management Plant (HBBMP) site. The site is owned by the City of Austin and is located about 3 km north of the Austin-Bergstrom International Airport. Field tests presented in this study were performed in an area named the Lower Tract B at the HBBMP site. The ground water table is about 10 m below the ground surface. Disturbed and undisturbed soil samples were recovered within the depth range of the sensor array (1 to 1.5 m) for soil classification. The soil in this depth range has: (1) a total unit weight of 17.5 kN/m³, (2) a natural water content of 22%, (3) a liquid limit of 29%, and (4) a plasticity index of 10%. Results of a hydrometer test show that 22% of the soil particles are fine sand, 78% passing the No. 200 sieve (0.075 mm), and 31% of these fines are clayey sized (<0.002 mm). The soil is classified as a low-plasticity clay (CL) in the Unified Soil Classification System (USCS). For the purpose of this project, which is to develop a method of simultaneously measuring linear and nonlinear shear moduli, the clayey soil at the site works well, because only one variable, nonlinearity in the soil skeleton as shear strain increases, is affecting the small-strain stiffness of the soil skeleton since the soil is unsaturated.

3 TEST EQUIPMENT

Two, hydraulic mobile shakers and eight, custom-built, 3-D motion sensors were used in these field studies. The shakers and motion sensors are part of the dynamic loading and sensing equipment at the NHERI@UTexas experimental facility (Stokoe et al. 2017). This equipment, which is available as shared-use equipment to any researcher with an NSF-funded project, is discussed below.

3.1 *Hydraulic mobile shakers*

Two, hydraulic mobile shakers, named Rattler and Thumper, were used to apply horizontal shaking loads on the ground surface which, in turn, created two sets of vertically propagating shear waves that passed through an embedded array of sensors below the shakers. Photographs of Rattler and Thumper are presented in Figures 1a and 1b, respectively. Rattler is a 22 metric-ton, off-road vehicle upon which a moderate-sized, horizontal shaker is mounted. Rattler is capable of shaking horizontally in the cross-line direction (the direction perpendicular to the longitudinal axis of the mobile shaker) with a maximum shear force of 133 kN over frequencies ranging from 6 and to 80 Hz. Thumper is a 10 metric-ton, International-model 4300 truck to which a small-sized shaker is mounted at the rear of the truck. Thumper is capable of shaking horizontally in either the in-line or cross-line directions with a maximum shear force of 26 kN over frequencies ranging from 17 to 300 Hz.

3.2 *Sensor array*

Eight, custom-built, 3-D motion sensors were used in these studies to create an embedded array of 3-D sensors. This array, shown in Figure 2a, was used to measure ground motions in




Figure 1. Two hydraulic mobile shakers operated by the NHERI@UTexas equipment facility that were used to evaluate G_{max} continuously during each cycle of large-strain shaking.




Figure 2. Instrumentation used for recording ground motions within the embedded array.

the X, Y, and Z directions. A photograph of one, 3-D sensor is shown in Figure 2b. Each 3-D sensor is composed of: (1) three, 28-Hz geophones to measure particle velocities in the X, Y, and Z directions, and (2) a 3-D MEMS accelerometer to measure tilt in the X and Y directions during sensor installation. The tilt measurements are used to calculate deviations in the horizontal directions as each sensor is pushed into the ground. With this information, the final installed locations are determined. The three geophones and MEMS accelerometer were epoxied in a custom-built, polycarbonate, cone-shape housing which is shown in Figure 2b.

As shown in Figure 2a, four of the 3-D motion sensors (3G, 4G, 5G and 6G) were installed at a depth of 1 m, and another four of the 3-D motion sensors (1G, 2G, 7G and 8G) were installed at a depth of 1.5 m. A hydraulic ram mounted at the rear of a third mobile shaker (named T-Rex) was used to push the sensors into the ground. The two sets of four sensors were installed to form two parallel trapezoids in the X-Z plane that were 0.9 m apart laterally. A top view and a cross-sectional view of the sensor array are shown in Figures 3a and 3b.

4 FIELD TESTING PROCEDURE AND EXAMPLE TIME RECORDS

During field testing, Thumper and Rattler were parked next to each other as shown in Figure 4a. The distance between the near edges of the baseplates of Rattler and Thumper was 1 m. Although not presented in the paper, different shaking configurations of the mobile shakers were investigated. It was found that by positioning the baseplate of Thumper over one trapezoidal sensor array (2G, 4G, 6G, and 8G) and by locating the baseplate of Rattler as close to the sensor array as possible, the small-amplitude motions generated by Thumper at 160 Hz were clearly recorded during the large-amplitude shaking motions induced by Rattler at 25 Hz (see Figure 4b). The resonant frequency of the field site was found to be 25 Hz. Hence, 25 Hz was chosen to maximize the shear strains generated with Rattler.

Three shaking events that were performed at the field site are discussed herein to illustrate the future use of this type of biaxial shaking. The conditions of the shaking events are summarized in Table 1. With both mobile shakers located as shown in Figure 4, testing began with small-strain uniaxial shaking using only Thumper. This testing condition, presented as Event 1 in Table 1, involved Thumper shaking at 160 Hz so that only small-strain shear moduli were




Figure 3. 3-D sensor array installed at the field test site in Austin, Texas.




Figure 4. Positions of the hydraulic shakers during the shaking tests.

determined. Then, biaxial shaking was performed using both Thumper and Rattler as presented in Events 2 and 3 in Table 1. Rattler was used to perform an increasing series of staged, higher-force shaking at 25 Hz in the Y direction while Thumper was shaking at 160 Hz in the X direction. This biaxial shaking condition allowed evaluation of the effects of larger shear strains in the Y direction on the small-strain shear modulus (G_{max}) in the X direction. In Events 2 and 3, the shakers were loading in perpendicular directions because it was found, as expected, that the signals are easier to process when the polarization of shear waves at two independent frequencies are in perpendicular directions. It is planned to investigate the effect of larger cyclic loading on the small-strain G_{max} values in the same plane in future testing.

Example time-displacement records collected with sensor 6G in the X and Y directions during Events 1 and 2 are shown in Figure 5. The displacement-time histories are integrated from the velocity-time histories. The time records in both the X and Y directions contain 5 tapered cycles at the beginning and end of each shaking event. The tapered cycles are applied to protect the hydraulic shakers from abrupt starting and stopping. In shaking Event 1 (Figures 5a and 5b), sensor 6G monitored the 160-Hz sinusoidal signal in the X direction and showed essentially no signal in the Y direction; hence, no cross-coupling in the 3-D sensor

Table 1. Shaking configurations and induced shear strains in three shaking events.

Event No.	Low level shaking with Thumper			High level shaking with Rattler		
	Shaking direction	Frequency Hz	Shear strain %	Shaking direction	Frequency Hz	Shear strain %
1	X	160	0.001	—	—	—
2	X	160	0.001	Y	25	0.01
3	X	160	0.001	Y	25	0.03




Figure 5. Time records of motion from sensor 6G in the X and Y directions when only Thumper was shaking (Event 1) and when both Thumper and Rattler were shaking (Event 2).

occurred at this shaking level. The 160-Hz sinusoidal signal was used to calculate the small-strain shear moduli using the SABW method as discussed in Section 6. In shaking Event 2 (Figures 5c and 5d), sensor 6G monitored the 160-Hz sinusoidal signal in the X direction (generated by Thumper) and the 25-Hz sinusoidal signal in the Y direction (generated by Rattler). During the steady-state shaking, the displacement amplitude of the 25-Hz shear-wave signal in the Y direction was about 7 times larger than the 160-Hz shear-wave signal in the X direction.

5 SHEAR STRAIN EVALUATIONS

Cyclic shear strains in the instrumented soil zone were calculated using the 3-D sensor array shown in Figure 3. Two different approaches were used in this study to evaluate shear strains. Rathje et al. (2005) categorized these two approaches as: (1) the displacement-based (DB) method, and (2) the wave propagation-based (WPB) method. The WPB method was used to analyze the 160-Hz, small-strain shaking by Thumper and the DB method was used to analyze the 25-Hz, larger-strain shaking created with Rattler as discussed below.

The wave propagation-based (WPB) method utilizes the ratio of particle velocity to wave-propagation velocity to compute shear strains. The assumption made in this computational procedure is that one-dimensional (1-D) stress wave propagation is occurring (also termed plane-wave propagation). The in-plane shear strain, γ , induced in the soil is simply:

$$\gamma = \frac{-\dot{u}}{V_{s,vh}} \quad (1)$$

where \dot{u} is the horizontal, in-line particle velocity, and $V_{s,vh}$ is the shear wave velocity of a vertically propagating, horizontally polarized shear wave. The minus sign in Equation 1 indicates that strain is 180 degrees out of phase with particle velocity.

The displacement-based (DB) method uses displacement-time histories measured with four motion sensors to evaluate shear-strain time histories. In this study, the four motion sensors were chosen to create an inclined rectangular array so that a 4-node iso-parametric element formulation could be applied to the plane in which the four sensors were located. For example, when Rattler is shaking in the Y direction in Event 2 and 3, four sensors (5G, 6G, 7G and 8G) are used as the four nodes of the inclined rectangular array to evaluate the shear strain in the soil between sensors 6G and 8G in the YZ plane.

Studies by Cox et al., 2009 show that larger shear strains are determined by the DB method because this method accounts for vertical displacements in motions created by rocking motions of the baseplate that occur during horizontal shaking. The DB method was, therefore, used to

calculate shear strains induced by Rattler shaking at 25 Hz. Although the DmB method is more reliable at larger shear strains, the DB method is not suitable for high-frequency, hence short-wavelength, measurements. When the wavelengths are less than 5 times the sensor spacing, the assumption of linear variable displacement used in the DB method is not valid (Rathje et al. 2005). In shaking Event 1, the SABW analysis (discussed in Section 6) shows that the average velocity of the sinusoidal, 160-Hz shear wave is 96 m/s. The resulting wavelength is 0.6 m, which is only 1.2 times the vertical spacing between geophone pairs (0.5 m). Hence, the WPB method is correctly used to calculate shear strains induced by low-amplitude Thumper shaking.

6 SPECTRAL-ANALYSIS-OF-BODY-WAVES (SABW) METHOD

The Spectral-Analysis-of-Body-Waves (SABW) method (Kim 2012) was implemented to permit determination of small-strain shear moduli continuously during the higher-strain cycling. The method is briefly outlined due to space limitations. Implementation of the method can be divided into two steps. The first step involves determining the phase shift in the frequency domain between the sinusoidal signals from the two receivers at different depths. Using the Fast Fourier Transform (FFT) algorithm, the time-domain records ($x(t)$ and $y(t)$) collected from two sensors are transformed into the frequency-domain ($X(f)$ and $Y(f)$). The transfer function, $H_{YX}(f)$, is determined as the ratio of $Y(f)$ over $X(f)$. The phase component, $\phi(f)$, of $H_{YX}(f)$ is calculated and indicates the phase shift between the time-domain records $x(t)$ and $y(t)$. In the second step, the unwrapped phase shift, ϕ , and the distance, d , that the shear wave traveled are used to calculate the wavelength of the shear wave ($\lambda = d \times (2\pi/\phi)$). Shear wave velocity, V_s , is simply $f \times \lambda$. Small-strain shear modulus, G_{max} , is simply calculated using the total unit weight, γ_t , gravitational acceleration, g , and V_s ($G_{max} = (\gamma_t/g) \times V_s^2$).

The analysis of two time-domain signals recorded by sensor pair 6G and 8G in shaking Event 1 is shown in Figure 6 to illustrate how G_{max} is calculated cycle by cycle using the SABW method. Particle velocity signals recorded by sensors 6G and 8G (depths of 1.0 and 1.5 m, respectively) in the X direction from 1.00 to 1.10 seconds are plotted in Figure 6a. Both signals contain 15 cycles of 160-Hz sinusoids, with the first six cycles designated by numbers 1 through 6. In Figure 6b, the truncated signals of the 6th cycle from both sensors are shown. The SABW procedure is used to calculate V_s and then G_{max} for the sixth cycle. The phase difference of the truncated signals was determined to be 5.3 radians. The vertical distance between sensors 6G and 8G in the array is 0.50 m. The wavelength is calculated to equal 0.60 m which results in a shear wave velocity equal to 96 m/s. The total unit weight of the soil is measured to be 17.5 kN/m³ so that a shear modulus of 16.5 MPa is calculated.

This SABW procedure is used to calculate shear wave velocities and shear moduli during every small-strain cycle at 160 Hz. The resulting shear wave velocities over cycles from 1.00 to 1.20 seconds are presented in Figure 6c. Each shear wave velocity value is plotted at the time in the middle of the two sinusoidal cycles. It can be seen in Figure 6c that the shear wave velocity is constant over these 30 cycles of small-strain uniaxial loading just as expected.




Figure 6. The SABW method used to evaluate the cycle-by-cycle, small-strain, shear wave velocities.

7 TEST RESULTS

The peak shear strains induced by Thumper and Rattler in the soil between sensors 6G and 8G during the three shaking events discussed in Section 4 are presented in Table 1. In uniaxial shaking Event 1, Thumper induced a peak shear strain of 0.001% in the instrumented soil zone in the XZ plane. The soil exhibited linear-elastic behavior at this small strain level. In biaxial shaking Events 2 and 3, Rattler generated shear strains of 0.01% and 0.03% in the YZ plane. In this case, the low-plasticity clay exhibited only mild nonlinear behavior in the YZ plane which was independent of number of loading cycles; hence, no degradation is exhibited. On the other hand, the values of G_{\max} in the XZ plane determined with the 160-Hz shaking did vary systematically as discussed below.

A hysteresis loop representing one cycle of the stress-strain relationship during the 25-Hz loading in the YZ plane in shaking Events 2 and 3 is schematically shown in Figure 7. The hysteresis loop is similar for shaking Events 2 and 3, only the slope and area change. (The values of G in the YZ plane were constant and were estimated from G/G_{\max} - $\log \gamma$ relationships to be 16.4 MPa and 13.6 MPa in Events 2 and 3, respectively.) The G_{\max} values in the XZ plane are denoted as G1 through G7 in Figure 7. (Note, G7 would be evaluated using the ending portion of one loop and the starting portion of the next loop.) The G_{\max} values were determined, on average, 6.4 times during each cycle of the 25-Hz stress-strain loops in the YZ plane. These G_{\max} values calculated from 1.0 to 1.5 seconds in the three shaking events are shown in Figure 8. In shaking Event 1 (Figure 8a), the small-strain shear moduli are constant over all loading cycles. In shaking Events 2 and 3 (Figures 8b and 8c), it is seen that the values of G_{\max} fluctuate sinusoidally at a frequency of 25 Hz, the frequency of the larger-amplitude shaking.

The systematic oscillation of G_{\max} in the XZ plane in Events 2 and 3, the decrease in the average value of G_{\max} in the XZ plane as shear strain increases in the YZ plane, and the lack of any




Figure 7. Schematic representation of small-strain shear moduli in the XZ plane during one, high-amplitude loading cycle generated by Rattler in the YZ plane.




Figure 8. Small-strain shear moduli evaluated by the SABW method at 160 Hz in the XZ plane.

changes during Events 2 and 3 with number of cycles (hence, no degradation) combine to show the potential of this field method to help characterize the soil skeleton during nonlinear loading processes. However, more field investigations are required, and this research is continuing.

8 CONCLUSIONS

During field shaking tests to determine soil liquefaction, the shear modulus of the sandy soil decreases as a result of both nonlinearity in the soil skeleton and decreasing effective stress due to increasing pore-water pressure. To better understand the impact of these two processes, an improvement to the field liquefaction testing method that involves two hydraulic mobile shakers is being developed. The goal is to measure the variation of small-strain shear moduli of the soil skeleton during cycles of higher-amplitude shaking. The small-strain shear moduli are measured in a plane perpendicular to that of the larger-strain shaking. In these initial tests which only involved unsaturated clayey soil, the improved field method was shown to be capable of measuring the reduction in the small-strain shear moduli of the soil skeleton due to the effect of higher-amplitude shaking. In future work, the reduction in the small-strain shear modulus of the soil skeleton due to the combination of pore-water pressure generation and nonlinearity in soil skeleton will be studied.

ACKNOWLEDGEMENTS

The authors would like to thank the U.S. National Science Foundation (NSF) for the financial support to develop and operate the NHERI@UTexas Equipment under grants CMS-0086605, CMS-0402490, and CMMI-1520808 and the financial support for this research project under grant CMMI-1663654. Special thanks also go to the staff at the University of Texas at Austin including Mr. Andrew Valentine and Mr. Robert Kent who assisted in the field work.

REFERENCES

- Cox, B.R., Stokoe, K.H., & Rathje, E.M. 2009. An In Situ Test Method for Evaluating the Coupled Pore Pressure Generation and Nonlinear Shear Modulus Behavior of Liquefiable Soils. *Geotechnical Testing Journal* 32(1): 11–21.
- Kim, C.Y. 2012, Development of the Spectral-Analysis-of-Body-Waves (SABW) Method for Downhole Seismic Testing with Boreholes or Penetrometers. *Ph.D. Dissertation*. The University of Texas at Austin, Austin, Texas, USA.
- Rathje, E.M., Chang, W.J. & Stokoe, K.H. 2005. Development of an In Situ Dynamic Liquefaction Test. *ASTM Geotechnical Testing Journal* 28(1): 50–60.
- Roberts, J.N., Stokoe, K.H., Cox, B., & Menq, F. 2017. Field and Laboratory Investigations into the Behaviors of Silty Sands that Leads to Liquefaction Triggering. *Proc. of 16th World Conference on Earthquake*, Santiago, Chile.
- Stokoe, K.H., Roberts, J.N., Hwang, S., Cox, B., Menq, F. & Van Ballegooy, S. 2014. Effectiveness of inhibiting liquefaction triggering by shallow ground improvement methods: Initial field shaking trials with T-Rex at one site in Christchurch, New Zealand. *New Zealand – Japan Workshop on Soil Liquefaction during Recent Large-Scale Earthquakes, Auckland*: 193–202.
- Stokoe, K.H., Cox, B.R., Clayton, P. & Menq, F. 2017. NHERI@UTEXAS experimental facility: large-scale mobile shakers for natural-hazards field studies. *Proc. of 16th World Conference on Earthquake*, Santiago, Chile.